



US Fabrics & AASHTO M288-00 Selection Guide

AASHTO M288-00 Geotextile Application	Survivability Class					
	CLASS 1		CLASS 2		CLASS 3	
	Woven (<50%)	Nonwoven (>50%)	Woven (<50%)	Nonwoven (>50%)	Woven (<50%)	Nonwoven (>50%)
Subsurface Drainage						
% Fines						
< 15%	US 230	US 205NW	US 230	US 160NW	US 230	US 120NW / US 115 NW
15% to 50%	n/a	US 205NW	US 670	US 160NW	US 670	US 120NW / US 115 NW
>15%	n/a	US 205NW	US 670	US 160NW	US 670	US 120NW / US 115 NW
Stabilization	US 315	US 205NW	US 250	US 160NW	US 200	US 120NW / US 115 NW
Separation	US 315	US 205NW	US 250	US 160NW	US 200	US 120NW / US 115 NW
Permanent Erosion Control						
% Fines						
< 15%	US 230	US 205NW	US 230	US 160NW	US 230	US 120NW / US 115 NW
15% to 50%	n/a	US 205NW	US 670	US 160NW	US 670	US 120NW / US 115 NW
>50%	n/a	US 205NW	US 670	US 160NW	US 670	US 120NW / US 115 NW

Paving Fabrics	US 100P
-----------------------	---------

*Default Classes are indicated by bold lettering.