




# AWD Fitting & Joint Tape

## Fitting & Joint Tape

GEOCOMPOSITE  
DRAIN



AWD Fitting & Joint Tape is recommended for the sealing, seaming, terminating, and connection of AWD Fittings and AWD geocomposite drainage products as referenced in AWD literature, including installation guides, CAD details, and technical bulletins. AWD Fitting & Joint Tape is designed for underground use and provides a strong bond that will not deteriorate over time in typical subsurface conditions.



- 40 mil thick composite member.
- Reinforced polyolefin base, laminated to a polypropylene layer.
- Adhesive-backed with removable release liner.

PROPERTY	TEST METHOD	ENGLISH	METRIC
Mullen Burst	ASTM 0751-95	180 x 1,240.92 psi	kPa
Trapezoidal Tear	ASTM 04533-91	46 x 44 lbs	205 x 196 N
Tensile Strength	ASTM 0751-95	130 x 124 lbs	579 x 552 N
Permeability (MVTR)	ASTM E96-8	0.075 Perms	0.075 Perms
Recycled Content	Calculated	45 %	45 %
UV Resistance @ 2,000 Hours	ASTM G154-98	90 %	90 %

## AWD Fitting & Joint Tape Shipping & Packaging Information

SIZE
4" x 75'

**US Fabrics, Inc. | 3904 Virginia Avenue | Cincinnati, OH 45227**  
**Phone: (800) 518-2290 | Fax: (513) 271-4420 | email: [info@usfabrics.com](mailto:info@usfabrics.com)**

This information is provided for reference only and is not intended as a warranty or guarantee.  
US Fabrics assumes no liability in connection with the use of this information.