





SGU200

Uni-Axial Knitted Geogrid

RETAINING WALL



STRATAGRID SGU200 (formerly SG1200) is geogrid reinforcement for soil. These high performance geogrids are constructed of high molecular weight and high tenacity polyester yarns utilizing a complex knitting process and polymer coating to provide superior engineering properties. Yarns are precision knitted into a dimensionally stable, uniform network of apertures providing significant tensile reinforcement capacity. STRATAGRID is engineered to be mechanically and chemically durable, in both the harsh construction installation phase and in aggressive soil environments (pH range from 3-9). STRATAGRID SGU200 meets the following properties:



PROPERTY	TEST METHOD	ENGLISH	METRIC
Ultimate Tensile Strength	<u>ASTM D-6637 Meth. A</u>	13,704 lbs/ft	199.99 kN/m
Creep Limited Strength	<u>ASTM D-5262/D-6992</u>	9,451 lbs/ft	137.98 kN/m
Long Term Design Strength (Sands, Silt and Clay)	LTDS	7,811 lbs/ft	114.04 kN/m
Carboxyl End Group Count Maximum	GRI GG7, ASTM D7409	30 Meg/kg	30 Meg/kg
Molecular Weight Minimum	GRI GG8	25,000 g/mole	25,000 g/mole
Reduction Factor - Creep (20°C, 114 years design life)		1.45	1.45
Reduction Factor - Environmental Effects Environment, 3<pH<9 (FHWA/AASHTO 1.15-1.30)	GRI-GG7, GRI-GG8	1.1	1.1
Reduction Factor - Installation Damage (sand/silt/clay)	ASTM D 5818	1.1	1.1

SGU200 Shipping & Packaging Information

SIZE	DIAMETER	WIDTH	WEIGHT	AREA	ROLLS PER TRAILER
12.5' x 288'	16"	12.5'	454 lbs	400 y ²	94

US Fabrics, Inc. | 3904 Virginia Avenue | Cincinnati, OH 45227
Phone: (800) 518-2290 | Fax: (513) 217-4420 | email: info@usfabrics.com

This information is provided for reference only and is not intended as a warranty or guarantee.
 US Fabrics assumes no liability in connection with the use of this information.